ejendals.com



TEGERA[®] 18601

SAFE BARRIER AGAINST MANY CHEMICALS

Chemical protection nitrile glove, with diamond grip for versatile duties. 0,38mm-thin nitrile acts as a barrier against many chemicals. Diamond pattern on the palm for better grip in wet and oily jobs. The flocked lining helps reduce sweat for the user. Latex-free for reduced risk of allergy and fully compliant for food handling.

| CHARACTERISTICS | FUNCTIONS | | | | | |
|-----------------|----------------------------------|--|--|--|--|--|
| • Good fit | Pre-curved fingers | | | | | |
| • Flexible | Approved for handling foodstuffs | | | | | |
| • Durable | Protection against chemicals | | | | | |
| Good grip | Latex-free | | | | | |
| Comfortable | Phthalate-free | | | | | |
| | | | | | | |







TEGERA[®]

PREVENTS RISK OF

risk of infection, corrosive injuries, contact with chemicals, contact with moisture, contact with damp, contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

chemical risk environments, microbiological risk environments, environments hazardous to health, corrosive environments, wet environments, moist environments, oily and greasy environments, dirty environments

PRIMARY AREAS OF USE

painting, agricultural work, petro-chemical work, chemical work, chemical technology work, laboratory work, paint spraying work

PRIMARY INDUSTRIES OF USE

agriculture, mining, oil, gas, petrochemical, pulp and paper, chemical, rubber and plastic, automotive

TYPE OF WORK

Medium weight

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

SPECIFICATION

TYPE Chemical protection gloves CATEGORY Cat. III THICKNESS 0,38 mm LENGTH 330 mm INSIDE Flock-lined GRIP DESIGN Diamond grip pattern COLOUR Green PAIRS PER: BUNDLE/CARTON 12/144 DISPLAY TYPE Bulk pack DIPPING MATERIAL Nitrile







Information/UIS

EN ISO 21420:2020



EN ISO 374-5:2016



EN 388:2016+A1:2018



TEST ACCORDING TO EN ISO 374-1:2016

| Tested chemical | J | Κ | L | Ν | 0 | Т |
|------------------|------|-----|------|------|--------|------|
| Permeation level | 6 | 6 | 2 | 2 | 4 | 6 |
| Degradation % | 15,7 | 8,9 | 86,1 | 94,6 | 5 34,4 | 33,9 |

| SIZE | ARTICLE NUMBER | EAN | | | |
|------|-------------------|---------------|--|--|--|
| 7 | 18601-7 | 7392626074262 | | | |
| 8 | 18601-8 | 7392626074286 | | | |
| 9 | 18601-9 | 7392626074309 | | | |
| 10 | 18601-10 | 7392626074248 | | | |
| 11 | 18601-11 | 7340118312019 | | | |



Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com