Datasheet



Respiratory protection

AIRCLEAN SM100 FFP1 NR D

Particle filtering half mask

The filtering half mask AIRCLEAN SM100 FFP1 NR D is designed to protect the respiratory system against aerosols of solid particles, water-based aerosols (dust, smoke) and aerosols with liquid dispersed phase (mists), provided that the concentration of the dispersed phase does not exceed 4 x TLV.

Your advantages

- The half mask is designed in such a way as to enable easy breathing throughout the work shift.
- The anatomical shape and the nose clip, as well as the internal sealing foam, make the half mask easy to fit to most face shapes, so that the necessary tightness can be ensured.

Δ

Your workspace

• The filtering half mask can be used in agriculture food industry, non-toxic dusts, quarries and cement plants, softwood processing (coniferous) and in particular for dusts like calcium carbonate, natural and synthetic graphite, gypsum, chalk, cement, plaster, marble, zinc oxide, pollen, cellulose, sulphur, cotton, metallic file dust, coal dust, coal dust with free silica content of less than 10%.

Product name		ltem no.	
AIRCLEAN SM100 FFP	1 NR D	AS4-SM100-FFP1	
Specifications			
Material Filter Head b	ands	Polypropylene Plastic	
Nose s		Polyurethane foam	
Functional parameters			
Class (according to EN 149:2001+A1:2009)			FFP1
Penetration of filtering material by sodium chloride aerosol or oil mist \$\$20%			
Total leakage			≤ 22%
Initial inhalation resistance at a flow of 95 I/min			≤ 210 Pa
Initial exhalation resistance 160 l/min			≤ 300 Pa
Breathing resistance at the end of clogging test with dolomite dust, at a flow of 95 l/min (inhalation)			≤ 300 Pa
Breathing resistance at the end of clogging test with dolomite dust, at a flow of 160 l/min (exhalation) ≤ 300 F			
Standards and certificates			
Category	Prote	ective masks	
Certifications/standa	r ds EN 14	49:2001+A1:2009	
Category PPE	Cate	gory III	
Testing institute	CIOP	– Notified Body 1437	
Packaging information			
Packaging unit		e / Box with 10 pieces oxes in a carton	

Customs tariff number63079099Country of originPL

Errors, printing errors and technical changes excluded. All information is based on extensive tests: No legally binding effect can be derived from it. We supply products and services exclusively in accordance with our General Terms & Conditions (GTC), which we would be happy to send you on request and are available on our website artiluxswisssafety.com.



ARTILUX Swiss Safety (ASS) AG Industriestrasse 15 CH-4410 Liestal

Tel. +41 61 906 90 00 Fax +41 61 901 79 82 sales@artiluxswisssafety.com artiluxswisssafety.com