Datasheet



Respiratory protection

AIRCLEAN SM280 FFP2 R D

Particle filtering half mask

The filtering half mask AIRCLEAN SM280 FFP2 R D is designed to protect respiratory system against harmful effect of dust, solid and particles when the concentration of dispersed phase of aerosol does not exceed 10 x TLV.



Your advantages

- The half mask is designed in such a way as to enable easy breathing throughout the work shift
- The anatomical shape and the nose clip, as well as the internal sealing foam, make the half mask easy to fit to most face shapes, so that the necessary tightness can be ensured.



Your workspace

 Medium toxic solids, asbestos, copper, barium, titanium, vanadium, chromium, manganese, hardwood, coal dust with free silica content higher than 10%, mining industry, chemical industry, metallurgic industry, welding, soldering, respirable dusts. Waste sorting, battery production, painting and interior decorating, wastewater treatment plants.

| Product name | Item no. |
|-------------------------|----------------|
| AIRCLEAN SM280 FFP2 R D | AS4-SM280-FFP2 |
| | |

| Specifications | | |
|----------------|---|--|
| Material | Filter Exhalation valve Head bands Nose seal | Polypropylene Plastic Plastic Polyurethane foam |

| Functional parameters | |
|--|----------|
| Class (according to EN 149:2001+A1:2009) | FFP2 |
| Penetration of filtering material by sodium chloride aerosol or oil mist | ≤ 6% |
| Total leakage | ≤ 8% |
| Initial inhalation resistance at a flow of 95 I/min | ≤ 240 Pa |
| Initial exhalation resistance 160 I/min | ≤ 300 Pa |
| Breathing resistance at the end of clogging test with dolomite dust, at a flow of 95 l/min (inhalation) | ≤ 500 Pa |
| Breathing resistance at the end of clogging test with dolomite dust, at a flow of 160 l/min (exhalation) | ≤ 300 Pa |
| | |

| Standards and certificates | | |
|----------------------------|--|--|
| Category | Protective masks | |
| Certifications/standards | EN 149:2001+A1:2009 | |
| Category PPE | Category III | |
| Testing institute | CIOP – Notified Body 1437 | |
| Packaging information | | |
| Packaging unit | Piece / Box with 10 pieces 36 boxes in a carton | |
| Customs tariff number | 63079099 | |

Errors, printing errors and technical changes excluded. All information is based on extensive tests: No legally binding effect can be derived from it. We supply products and services exclusively in accordance with our General Terms & Conditions (GTC), which we would be happy to send you on request and are available on our website artiluxswisssafety.com.

PL



Country of origin